


QUICK-CONNECT
VON BALS

Panelintag 75x75 Quick-Connect

Specifikation

MATERIAL KAPSLING	Polyamid PA6
MATERIAL TERMINALER	Mässing
ANSLUTNINGSBAR AREA	16A max. 2,5mm ² 32A max. 6mm ²
SKYDDSKLASS	IP44
HALOGENFRI	Ja

Varianter

E-NUMMER	ARTIKELNR	BESKRIVNING	ANTAL POLER	DRIFTSPÄNNING / FÄRGKOD	MÄRKSTRÖM A	FÄSTHÅLS AVSTÅND MM	ANTAL/FÖRP
2421755	28111	216-6	3	230V / Blå	16	60 x 60	10
-	28017	316-9	4	230V / Blå	16	60 x 60	10
-	28006	416-9	5	230V / Blå	16	60 x 60	10
2421758	28010	232-6	3	230V / Blå	32	60 x 60	10
-	28011	332-9	4	230V / Blå	32	60 x 60	10
-	28015	432-9	5	230V / Blå	32	60 x 60	10
2421756	28112	316-6	4	400V / Röd	16	60 x 60	10
2421757	282001	416-6	5	400V / Röd	16	60 x 60	10
2421759	28012	332-6	4	400V / Röd	32	60 x 60	10
2421760	282002	432-6	5	400V / Röd	32	60 x 60	10