


QUICKCONNECT
VON BALS

Väggtag Quick-Connect

Specifikation

MATERIAL KAPSLING	Polyamid PA6
MATERIAL TERMINALER	Mässing
ANSLUTNINGSBAR AREA	16A max. 2,5mm ² 32A max. 6mm ²
SKYDDSKLASS	IP44
HALOGENFRI	Ja

Varianter

E-NUMMER	ARTIKELNR	BESKRIVNING	ANTAL POLER	DRIFTSPÄNNING / FÄRGKOD	MÄRKSTRÖM A	KABEL GENOMFÖRING MM	ANTAL/FÖRP
2421730	24423	216-6	3	230V / Blå	16	M20	10
-	24393	316-9	4	230V / Blå	16	M25	10
-	24400	416-9	5	230V / Blå	16	M25	10
2421733	24402	232-6	3	230V / Blå	32	M25	10
-	24404	332-9	4	230V / Blå	32	M25	10
-	24407	432-9	5	230V / Blå	32	M25	10
2421731	24392	316-6	4	400V / Röd	16	M25	10
2421732	242001	416-6	5	400V / Röd	16	M25	10
2421734	24405	332-6	4	400V / Röd	32	M25	10
2421735	242002	432-6	5	400V / Röd	32	M25	10