



## Reducering Mässing Hexagonal Metrisk-Metrisk

### Specifikation

MATERIAL	Förnicklad mässing (CuZn39Pb3)
O-RING	Nitrilgummi NBR
TEMPERATUROMRÅDE	-40°C...+100°C
FÄRG	Förnicklad Mässing
HALOGENFRI	Ja

## Varianter

ARTIKELNR	YTTERGÄNGA	INNERGÄNGA	L MM	H MM	SWI MM	EI MM	ANTAL/FÖRP
M16M12/6/OM	M16x1,5	M12x1,5	5	8	17	19	100
M20M12/6/OM	M20x1,5	M12x1,5	6	9	22	24,5	100
M20M16/6/OM	M20x1,5	M16x1,5	6	9	22	24,5	100
M25M16/6/OM	M25x1,5	M16x1,5	7	10	27	30	100
M25M20/6/OM	M25x1,5	M20x1,5	7	10	27	30	100
M32M16/6/OM	M32x1,5	M16x1,5	8	11	34	36	50
M32M20/6/OM	M32x1,5	M20x1,5	8	11	34	36	50
M32M25/6/OM	M32x1,5	M25x1,5	8	11	34	36	50
M40M20/6/OM	M40x1,5	M20x1,5	8	12	43	46	25
M40M25/6/OM	M40x1,5	M25x1,5	8	12	43	46	25
M40M32/6/OM	M40x1,5	M32x1,5	8	12	43	46	25
M50M25/6/OM	M50x1,5	M25x1,5	9	13	55	60	10
M50M32/6/OM	M50x1,5	M32x1,5	9	13	55	60	10
M50M40/6/OM	M50x1,5	M40x1,5	9	13	55	60	10
M63M32/6/OM	M63x1,5	M32x1,5	10	14	65	70	10
M63M40/6/OM	M63x1,5	M40x1,5	10	14	65	70	10
M63M50/6/OM	M63x1,5	M50x1,5	10	14	65	70	10