



Adapter Mässing Metrisk - PG

Specifikation

MATERIAL	Förnicklad mässing (CuZn39Pb3)
O-RING	Nitrilgummi NBR
SKYDDSKLASS	IP68
TEMPERATUROMRÅDE	-30°C...+100°C
FÄRG	Förnicklad Mässing
HALOGENFRI	Ja

Varianter

E-NUMMER	YTTERGÅNGA	INNERGÅNGA	L1 MM	D2 MM	DI MM	L2 MM	L3 MM	L4 MM	ANTAL/FÖRP
1476481	M12x1,5	PG9/15,2	5	17	8	16	7	9	100
1476482	M16x1,5	PG11/18,6	5	20	12	16,5	7	9,5	100
1476483	M20x1,5	PG16/22,5	6	24	15	19,5	7,5	11,5	100
1476484	M25x1,5	PG21/28,3	7	30	21	21,5	8,5	13	50
1476485	M32x1,5	PG29/37,0	8	39	26	25	9	14,5	50
1476486	M40x1,5	PG36/47,0	8	50	34	28,5	12	17,5	25
1476487	M50x1,5	PG42/54,0	9	57	44	32	15	20	10
1476488	M50x1,5	PG48/59,3	9	64	44	33	17	21	10