



Avslutningspropp Mässing IP54 PG

Specifikation

| | |
|-------------------------|--------------------------------|
| MATERIAL | Förnicklad mässing (CuZn39Pb3) |
| SKYDDSKLASS | IP54 |
| TEMPERATUROMRÅDE | -60°C...+200°C |
| FÄRG | Förnicklad Mässing |
| HALOGENFRI | Ja |

Varianter

| E-NUMMER | YTTERGÅNGA | L MM | L1 MM | DA MM | DI MM | H MM | ANTAL/FÖRP |
|----------|------------|------|-------|-------|-------|------|------------|
| 1466117 | PG7/12,5 | 5 | 5 | 14 | 10 | 8 | 100 |
| 1466115 | PG9/15,2 | 6 | 6 | 17 | 11,8 | 9 | 100 |
| 1466118 | PG11/18,6 | 6 | 6 | 20 | 15 | 9 | 100 |
| 1466120 | PG13/20,4 | 6,5 | 6,5 | 22 | 17 | 9,5 | 100 |
| 1466122 | PG16/22,5 | 6,5 | 6,5 | 24 | 18,5 | 9,5 | 100 |
| 1466128 | PG21/28,3 | 7 | 7 | 30 | 24 | 11 | 100 |
| 1466137 | PG29/37,0 | 8 | 8 | 39 | 32 | 12 | 50 |
| 1466147 | PG36/47,0 | 9 | 9 | 50 | 42 | 15 | 25 |
| 1466148 | PG42/54,0 | 10 | 10 | 57 | 48 | 16 | 25 |
| 1466149 | PG48/59,3 | 10 | 10 | 64 | 53 | 16 | 10 |