



Reducering Mässing PG - PG

Specifikation

MATERIAL	Förnicklad mässing (CuZn39Pb3)
TEMPERATUROMRÅDE	-60°C....+200°C
FÄRG	Förnicklad Mässing
HALOGENFRI	Ja

Varianter

E-NUMMER	YTTERGÄNGA	INNERGÄNGA	L MM	L1 MM	D MM	H MM	ANTAL/FÖRP
907	PG9/15,2	PG7/12,5	6	2,5	17	8,5	100
1107	PG11/18,6	PG7/12,5	6	2,5	20	8,5	100
1463950	PG11/18,6	PG9/15,2	6	2,5	20	8,5	100
1307	PG13,5/20,4	PG7/12,5	6,5	2,5	22	9	100
1463951	PG13,5/20,4	PG9/15,2	6,5	2,5	22	9	100
1463952	PG13,5/20,4	PG11/18,6	6,5	2,5	22	9	100
1607	PG16/22,5	PG7/12,5	6,5	3	24	9,5	100
1463954	PG16/22,5	PG9/15,2	6,5	3	24	9,5	100
1463956	PG16/22,5	PG11/18,6	6,5	3	24	9,5	100
1463957	PG16/22,5	PG13,5/20,4	6,5	3	24	9,5	100
1463958	PG21/28,3	PG11/18,6	7	3	30	10	100
2113	PG21/28,3	PG13,5/20,4	7	3	30	10	100
1463960	PG21/28,3	PG16/22,5	7	3	30	10	100
1463962	PG29/37,0	PG16/22,5	8	3,5	39	11,5	50
1463964	PG29/37,0	PG21/28,3	8	3,5	39	11,5	50
3621	PG36/47,0	PG21/28,3	9	3,5	50	12,5	25
1463966	PG36/47,0	PG29/37,0	9	3,5	50	12,5	25
1463965	PG42/54,0	PG29/37,0	10	4	57	14	10
1463967	PG42/54,0	PG36/47,0	10	4	57	14	10
1463968	PG48/59,3	PG36/47,0	10	4	64	14	10
1463969	PG48/59,3	PG42/54,0	10	4	64	14	10