



Reducering Polyamid RAL 7035 PG - PG

Specifikation

MATERIAL	Polyamid PA6 glasfiberförstärkt
TEMPERATUROMRÅDE	-30°C...+100°C
FÄRG	Ljusgrå RAL 7035
HALOGENFRI	Ja

Varianter

E-NUMMER	YTTERGÅNGA	INNERGÅNGA	L MM	T MM	D MM	H MM	SW MM	E MM	ANTAL/FÖRP
1464315	PG9/15,2	PG7/12,5	8	9,5	7	20,5	19	20,7	100
1464317	PG11/18,6	PG7/12,5	8	9	7,5	14	22	24	100
1464318	PG11/18,6	PG9/15,2	8	11	10	22	22	24,8	100
1464319	PG13,5/20,4	PG7/12,5	9	9,5	7,5	15	24	26	100
1464321	PG13,5/20,4	PG9/15,2	9	9	10	15	24	26	100
1464320	PG13,5/20,4	PG11/18,6	9	12	11,5	24	24	26	100
1464322	PG16/22,5	PG9/15,2	10	10	10	16	27	29	100
1464323	PG16/22,5	PG11/18,6	10	9	11,5	16	27	29	100
1464324	PG16/22,5	PG13,5/20,4	10	13,5	13	27	27	29	100
1464328	PG21/28,3	PG11/18,6	11	10,5	11,5	16	32	35,5	100
1464327	PG21/28,3	PG13,5/20,4	11	10,5	13,5	16	32	35,5	100
1464329	PG21/28,3	PG16/22,5	11	11	15,5	16	32	35,5	100
1464336	PG29/37,0	PG13,5/20,4	11	12,5	14	17	40	43	50
1464337	PG29/37,0	PG16/22,5	11	12,5	17	17	40	43	50
1464338	PG29/37,0	PG21/28,3	11	13	22	17	40	43	50
1464345	PG36/47,0	PG16/22,5	13	12,5	18,5	19	50	54	50
1464346	PG36/47,0	PG21/28,3	13	13	21,5	19	50	54	50
1464347	PG36/47,0	PG29/37,0	18	18,5	30,5	24	50	54	50
1464354	PG42/54,0	PG21/28,3	18	12,5	21,5	24	55	60	25
1464355	PG42/54,0	PG29/37,0	18	18,5	28	24	55	60	25
1464356	PG42/54,0	PG36/47,0	18	18	39	24	55	60	25
4829PA	PG48/59,3	PG29/37,0	18	17,5	30,5	24	60	65	25
4836PA	PG48/59,3	PG36/47,0	14	16	38,5	20	60	65	25
4842PA	PG48/59,3	PG42/54,0	17	18,5	42,5	23	60	65	25