



Avslutningspropp Polyamid IP54 RAL 9005 PG

Specifikation

MATERIAL	Polyamid 6 GF30 Glasfiberförstärkt
SKYDDSKLASS	IP54
TEMPERATUROMRÅDE	-40°C....+100°C
FÄRG	Svart RAL 9005
HALOGENFRI	Ja

Varianter

E-NUMMER	YTTERGÅNGA	L MM	LI MM	DA MM	DI MM	H MM	ANTAL/FÖRP
1007PA/SW	PG7/12,5	6	7	15	9	10	100
1009PA/SW	PG9/15,2	6	7	19	11,5	10	100
1011PA/SW	PG11/18,6	6	7	22	14	10	100
1013PA/SW	PG13,5/20,4	6	7	25	15,5	10	100
1016PA/SW	PG16/22,5	6	7	27	17	10	100
1021PA/SW	PG21/28,3	8	9	33	23	12,5	100
1029PA/SW	PG29/37,0	8	9	44,5	31,5	13	100
1036PA/SW	PG36/47,0	10	10	55,5	40,5	15	50
1042PA/SW	PG42/54,0	10	10	62,5	47,5	15,5	50
1048PA/SW	PG48/59,3	12	11,5	69,5	52,5	17	50

