



Förstoring Polyamid RAL 7035 PG - PG

Specifikation

MATERIAL	Polyamid 6 glasfiberförstärkt
TEMPERATUROMRÅDE	-30°C...+100°C
FÄRG	Ljusgrå RAL 7035
HALOGENFRI	Ja

Varianter

E-NUMMER	YTTERGÄNGA	INNERGÄNGA	L MM	LI MM	DI MM	H MM	SW MM	E MM	ANTAL/FÖRP
1464412	PG7/12,5	PG9/15,2	7	9,5	8,5	20	19	21	100
1464415	PG9/15,2	PG11/18,6	8	10	10	23	22	25	100
1464417	PG11/18,6	PG13,5/20,4	8	12,5	13,5	23	24	25	100
1464418	PG11/18,6	PG16/22,5	8	12,5	12,5	24,5	27	29,5	100
1464420	PG13,5/20,4	PG16/22,5	9	13,5	15	26	27	29,5	100
1464422	PG16/22,5	PG21/28,3	9	12	16	29	32	35,5	100
1464428	PG21/28,3	PG29/37,0	10	17	22,5	32	42	45,5	50
1464437	PG29/37,0	PG36/47,0	11	21,5	30,5	35,5	53	57	25
1464447	PG36/47,0	PG42/54,0	13	22	39,5	40,5	60	65	10
1464454	PG42/54,0	PG48/59,3	13	22,5	45,5	45,5	65	70,5	10